

General tolerances

Welded Constructions (DIN EN ISO 13920-B)

2 ~ 30	30 ~ 120	120 ~ 400	400 ~ 1000	1000 ~ 2000	2000 ~ 4000	0.5 ~ 3	3 ~ 6	6 ~ 30	30 ~ 120	120 ~ 140	140 ~ 400	400 ~ 1000
±1	±2	±2	±3	±4	±6	±0.1	±0.1	±0.2	±0.3	±0.5	±0.8	

R250

P X LINK = L

112

586

91

B

86

112

4-ø10.5X26 SLOTHHOLES

70

38

240
294

VIEW B

FIX BRACKET(S=1:1)

4-ø10.5X26 SLOTHHOLES


70

38

240
294

VIEW C

MOVE BRACKET(S=1:1)



SECTION A-A (S=1:1)

기호 MARK	일자 DATE	변경내역 DETAIL OF REVISION(E.C.ZONE)	설계번호 E.C NO.	설계 DGN	검토 CHK	승인 APP
△	-	-				
▽	-	-				
◇	-	-				

도면 NO.	품명 DESCRIPTION	차수 SIZE	재질 MATERIAL	UNIT	TOTAL QTY (수량)	PER UNIT W.T (중량)	TOTAL	비고 REMARKS
CUSTOMER & YARD		-						
승인 APP	N.H KIM '24.02.16	영역 TITLE	KC091-R250-W250-EBST					①
검토 CHK	N.H KIM '24.02.16	도면번호 DWG NO.	-					SHEET 1 of 1
설계 DGN		KBBE Co.,Ltd.						SCALE N/S
제도 DWG								